

Rollerblind QS22 Twin

Product information

Main feature of this model is the high user comfort, due to the easy and smooth operation and of course the low noise chain control system. Instead of one fabric this twin rollerblind has two fabrics in one cassette.



Technical information

Product Code	QS22.0		
Product Name	Twin rollerblind		
Operation	Chain Operation		
Tube	Material	Extruded Aluminium \varnothing 34mm	
Dimensions	Width	400mm min - 1800mm max	
	Drop	300mm min - 2800mm max	
	Maximum Area	5,04m ²	
Bottom Rail	Material	Extruded Aluminium Alloy- Asymetric Profile	
	Dimensions	12mm W x 19mm H	
	Colours	RAL 9001,,9010,9016 Anodised	
	Paint	Electrostatic Powdercoated and Baked	
Cassette	Material	Extruded Aluminium Alloy	
	Dimensions	106mm x 138mm	
End Caps	Material	UV Stabilised Polymer Acrylic	
	Colours	Grey,White,Black	
Chain	Material	Aluminium or Stainless Steel	
Installation Brackets	Material	Press formed steel, pre-treated and powder coated	
	Operation	Top or Face Fixing - concealed when installed	

Rollerblind QS22 Twin

Motorisation

Product Code	QS22.4	QS22.5	
Product Name	Standard Rollerblind	Standard Rollerblind	
Operation	24V DC Somfy	12V DC Somfy Battery	
Tube	Extruded Aluminium \varnothing 34mm	Extruded Aluminium \varnothing 34mm	
Dimensions	Width	400mm min - 1800mm max	400mm min - 1800mm max
	Drop	300mm min - 2800mm max	300mm min - 2800mm max
	Maximum Area	5,04m2	5,04m2

Optional

System diagrams

